



F & L ULTRA XTREME SHOCK OIL

Ultra high viscosity index, low pour point, ultra high temperature shock oil

Product Description

F& L Ultra Xtreme Shock Oil was developed for the severe duty demands of off-road racing. **F& L Ultra Xtreme Shock Oil** contains additives that provide excellent low & high temperature fluidity as well as exceptional anti-wear, oxidation – corrosion inhibition, and shear stability. In addition, metal deactivators and foam inhibitors are provided in this high viscosity index fluid to enhance performance for the challenges of xtreme off-road racing.

Applications

- Specifically formulated for off-road racing
- **F& L Ultra Xtreme Shock Oil** exceeds the demands of Xtreme off-road racing.

Features/Benefits

- Performs well in Xtreme high temperature applications where other shock oils fail
- Designed for Shocks subject to a wide variation in operating temperatures.
- Low-friction ultra-heat protection against shock fade
- Superior anti-wear protection
- Excellent oxidation stability
- Outstanding protection against rust and corrosion
- Non-foaming
- Rapid air separation

Compatibility

F& L Ultra Xtreme Shock Oil should not be used in shocks using natural rubber elastomers.

Typical Properties of F& L Ultra Xtreme Shock Oil

	Test Method	F& L Ultra Xtreme Shock Oil
Viscosity:		
@ 40°C, cSt	D 445	13.9
@ 100°C, cSt	D 445	5.13
Viscosity Index	D 2270	370
Gravity, °API @ 60°F	D 1298	29.3
Flash Point, COC, °F	D 92	203
Pour Point, °F	D 97	-70
Copper Corrosion	D 130	1b
Rust Test	D 665B	Pass

Notice: Since the conditions of handling and use are beyond our control, we make no guarantee of results, nor is any of the above information to be taken as a license to operate under, or recommendation to infringe upon, any patent. The information contained herein is, to the best of our knowledge and belief, accurate, but we assume no liability for damages or penalties resulting from use of or reliance on this information.